

Stratasys J4100

Create large or small production tools and full-scale prototypes.

Maximize your productivity and quickly achieve ROI with the Stratasys J4100™ 3D Printer. Its multimaterial capabilities, substantial throughput and ultra-large build tray help get jobs done faster, smarter and with more precision. Driven by PolyJet Technology™, this powerful system enables engineers, manufacturers and designers to 3D print any design – no matter how complex or detailed.

Part size is no object: the J4100 is equally adept at printing large or small prototypes with no compromise on precision. In one build, print large parts over one meter in length, eliminating the need to split large files in CAD and bond parts later. Print many parts in one job and enjoy a competitively low cost per part.

Reliable and easy to use, the J4100 helps you build parts that are ready for use with little or no post-processing. Support material is quick to remove with a WaterJet, and for most applications the smooth, multi-material parts require no polishing or painting

3D Printer Specifications

| | | |
|---------------------------|---|--|
| Model Materials | Neutral shades | Flexible materials |
| | <input type="checkbox"/> VeroPureWhite™ <input checked="" type="checkbox"/> VeroBlackPlus™ <input checked="" type="checkbox"/> VeroBlue™ <input checked="" type="checkbox"/> VeroGrey™ | <input checked="" type="checkbox"/> Agilus30 Black <input type="checkbox"/> Agilus30 Clear |
| Support Materials | Transparent materials | Digital materials |
| | <input type="checkbox"/> VeroClear™ <input type="checkbox"/> VeroUltraClear™ | <input checked="" type="checkbox"/> Digital ABS Plus™ Ivory <input checked="" type="checkbox"/> Digital ABS Plus™ Green |
| Support Materials | SUP705™ (WaterJet removable) | |
| Build Size | 1000 x 800 x 500 mm (39.4 x 31.5 x 19.7 in) | |
| Layer Thickness | Horizontal build layers range between 27 microns - 55 microns (0.001 in. - 0.002 in.) depending on the print mode. | |
| Workstation Compatibility | Windows 7 | |
| Network Connectivity | LAN – TCP/IP | |
| System Size and Weight | 1960 x 2868 x 2102 mm (77.5 x 113 x 83 in.) 22000 kg (4850 lbs.) | |
| Operating Conditions | Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30-70% (non-condensing) | |
| Power Requirements | 230 VAC 50/60 Hz, 8A single phase | |
| Regulatory Compliance | CE, FCC | |
| Software | GrabCAD Print™ with KATANA Slicer | |
| Build Modes | High Speed: up to 3 base resins, 27 micron (0.001 in.) resolution Super High Speed: 1 base resin, 55 micron (0.002 in.) resolution | |
| XY Resolution | 300x600 DPI | |



Stratasys Headquarters

7665 Commerce Way,
Eden Prairie, MN 55344
+1 800 801 6491 (US Toll Free)
+1 952 937-3000 (Intl)
+1 952 937-0070 (Fax)

stratasys.com

ISO 9001:2015 Certified

1 Holtzman St., Science Park,
PO Box 2496
Rehovot 76124, Israel
+972 74 745 4000
+972 74 745 5000 (Fax)

© 2020 Stratasys Ltd. All rights reserved. Stratasys, Stratasys signet, PolyJet Technology, Stratasys J4100, Digital ABS Plus, Agilus30, Vero, VeroClear, VeroUltraClear, SUP705 and GrabCAD Print are trademarks or registered trademarks of Stratasys Ltd. and/or its subsidiaries or affiliates and may be registered in certain jurisdictions. All other trademarks belong to their respective owners. Product specifications subject to change without notice. PSS_PJ_StratasysJ4100_1020a

